- Fully stainless steel frame and base built to handle washdown and corrosive environments with ease
- Easy-to-clean surfaces meet strict sanitation standards for food processing, pharmaceutical applications, and cleanroom facilities, with cGMP-compliant models available
- Built with slip-resistant flooring to enhance worker safety
- Space-saving design navigates easily around equipment in confined areas
- Designed to give workers easy, comfortable access to overhead work



Features

- Capacities from 500 lbs to 10,000 lbs and lift heights to 144”
- Tube and non tube units available
- Delrin rolles and Delrin bushings
- 100% grade 8 bolts

Model	Capacity (lbs)	Platform Size	Base Size	Lower Height	Raised Height	Up Speed (Seconds)	Motor HP	Shipping Weight (lbs)
60” Lifts								
DSL-SS-60-20	2,000	30” x 48”	30” x 48”	10”	70”	35	1	1,800
DSL-SS-60-40	4,000	30” x 48”	30” x 48”	14”	74”	70	1	1,800
DSL-SS-60-60	6,000	30” x 48”	30” x 48”	16”	76”	90	1	1,900
72” Lifts								
DSL-SS-72-20	2,000	30” x 60”	30” x 60”	10”	82”	45	1	2,000
DSL-SS-72-40	4,000	30” x 60”	30” x 60”	14”	86”	90	1	2,100
DSL-SS-72-60	6,000	30” x 60”	30” x 60”	16”	88”	110	1	2,200
84” Lifts								
DSL-SS-84-20	2,000	48” x 84”	48” x 72”	10”	106”	60	3	3,000
DSL-SS-84-40	4,000	48” x 84”	48” x 72”	14”	110”	70	3	3,100
DSL-SS-84-60	6,000	48” x 84”	48” x 72”	16”	70”	60	3	3,200
120” Lifts								
DSL-SS-120-20	2,000	48” x 96”	48” x 96”	10”	134”	30	5	3,000
DSL-SS-120-40	4,000	48” x 96”	48” x 96”	14”	134”	35	5	3,200
DSL-SS-120-60	6,000	48” x 96”	48” x 96”	16”	134”	35	5	3,800
144” Lifts								
DSL-SS-144-20	2,000	54” x 108”	54” x 108”	16”	160”	60	5	3,200
DSL-SS-144-40	4,000	54” x 108”	54” x 108”	16”	160”	60	5	3,400
DSL-SS-144-60	6,000	54” x 108”	54” x 108”	18”	162”	60	5	3,550

Terra Universal, Inc. • TerraUniversal.com • 800 S. Raymond Ave. Fullerton, CA 92831 USA • TEL: +1-714-578-6000 FAX: +1-714-578-6020