

ISO-Clean® Glider Door - Bi-Parting

The ISO-Clean Bi-Parting Glider Door improves on the technology of traditional cleanroom doors to deliver more value and low maintenance.

Our door sets the standard for excellence in the industry, offering superior durability, safety, and clean functionality that brings us to the forefront of the market.

Clean

With our advanced SmartSeal™ System, our door is designed with premium features as standard, aiding in environmental separation and control.

Safe

Innovative design and enhanced communication with our SafeAlert™ System.

Simple

Fewer moving parts and low maintenance.



Smart, Connected with Rite-Hite ONE

The Rite-Hite ONE Control Tower provides real-time visibility into data produced by Rite-Hite's line of smart, connected loading dock and high-speed door equipment, empowering customers to act on meaningful analytics that optimize facility throughput, prioritize maintenance, and help mitigate safety incidents.



SafeAlert System



Door-Commander™ Controls

Specifications

Speed

Bi-parting:

Open – 39" (991 mm) per second

Close – 14" (356 mm) per second

Size

Bi-parting:

Minimum – 6'0" w x 7'0" h (1829 mm x 2134 mm)

Maximum – Up to 10'0" w x 10'0" h (3048 mm x 3048 mm)

Electrical requirements

120V/1ph (20 Amp Service Required)

Panel design

1.75" (45 mm) thick white fiberglass panel with stainless steel edge capping and insulated foam core. Flush vision panels and stainless steel 12" high kickplates come standard.

Wireless interlock

Wireless interlock comes standard and locks up to (15) Rite-Hite Doors without the expense and hassle of hard wiring.

Header assembly

Header track assembly is aluminum (optional fully stainless steel). Available with standard multipiece stainless steel header shroud, with bolted seams and endcaps, or optional fully single piece, stainless steel header shroud. Electronic solenoid lock is optional.

Door-Commander™ Advanced Controls

The industry's only 10" (254 mm) LCD touch screen interface, flush mounted, that displays real time door status, and provides increased safety by allowing an individual to simply access the control box settings without wearing the necessary PPE often required for accessing a live electrical panel.

Safety features

SafeAlert™ System provides communication of the door status (counting down time until door auto-closes, door will not open due to interlock, door in fault status, etc.). SafeAlert System display mounted integrally in header comes standard. Two (2) thru-beam photo eyes at 18" (457 mm) and 54" (1372 mm) from floor. Torque sensing reverses the door back open if contact with personnel or equipment while closing.

Standard warranty

One (1) year for drive system.
Two (2) year on panel, electrical and mechanical components parts.
One (1) year labor.

Extended warranty

Two (2) year for drive system.
Three (3) year on panel, electrical and mechanical components parts.
Two (2) year labor.



RITEHITE
ALWAYS LOOKING AHEAD

5ISCGBIDISGSS0325AMEN01

Milwaukee, Wisconsin, USA

www.ritehite.com

P 414-355-2600 (800-456-0600)

F 414-355-9248

Rite-Hite®, ISO-Clean® Glider Door, SmartSeal™, SafeAlert™ System, i-COMM™, and Door-Commander™ Advanced Control System are trademarks of the Rite-Hite Holding Corporation. Rite-Hite products may be covered by one or more U.S. Patents with other U.S. and foreign patents pending. Patent coverage: www.ritehite.com/patents. The information herein is provided as a general reference only regarding the use of the applicable products. The specifications stated here are subject to change. Manufactured by Rite-Hite Doors, Inc.